


For further information, email
sales.aqua@imenco.com

imenco
AQUA



Labrus L

RELIABLE INSPECTION CAMERA FOR A **VARIETY** OF APPLICATIONS

Innovation based on acknowledged technology


The Imenco Aqua Labrus L is a robust, wide-angle IP inspection camera equipped with integrated LED lighting. Compact and straightforward to install, it provides reliable, high-quality imaging at a low cost, making it well-suited for inspection tasks across diverse marine and industrial applications.

Features

- Integrated LED lights
- Wide angle coverage
- Compact and lightweight
- Versatile

Advantages

- Built-in illumination ensures clear images even in dark or murky conditions
- Captures a broader field of view
- Easy to handle, install and deploy
- Suitable for multiple applications such as underwater inspections, monitoring and confined space observation



Technical Specifications

Video resolution	1080p @ 30fps
Video format	H.264 – RTP / RTSP / UDP
Latency (glass to glass)	≈ 250ms
Minimum illumination (DSS off)	0,2 lux
Angle of view in water	122° dia. / 115° hor.
Front port	Dome – BK7
LED lights	Fixed on or dimmable ¹
Light output	300 Lumen
Housing	POM (Delrin)
Depth rating	150m
Standard connector	Subconn DBH13
Power requirements	12VDC / 24VDC / 5W or PoE (separate models)
Main dimensions (ex. connector)	Ø 79 / 74 x 123mm (3.1 / 2.9 x 4.8 inches)
Weight in air	0.6 kg
Weight in water	0.2 kg

¹ Dimmable lights are only available on the 24V version of Labrus L